

# ECS3510-26T

## L2 Fast Ethernet Standalone Switch



### Product Overview

The Edge-Core ECS3510-26T is a high-performance Fast Ethernet Layer 2/4 switch featuring 24 10/100BASE-TX ports and 2 combination Gigabit Ethernet RJ-45/SFP (Small Form Factor Pluggable) ports. The switch is ideal for Fast Ethernet desktop connectivity and wiring closet installations. The switch is packed with features and is a cost-effective solution that brings continuous availability, enhanced security, and advanced QoS to the network edge, while maintaining simplicity of management.

### Key Features and Benefits

#### Performance and Scalability

This entry-level managed switch provides 8.8 Gbps wire-speed switching performance across all ports. This enables the switch to fully support existing high-performance PCs and laptops, which significantly improves application response times and the speed of large file transfers.

The two Gigabit Ethernet combination ports enable uplink flexibility, offering copper or fiber uplinks to servers or the network backbone.

#### Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol support provides loop-free and redundant links to the core network with rapid convergence, which ensures a faster recovery from failed links and enhances overall network stability and reliability.

The IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base (up to 32 instances), providing Layer 2 load sharing on redundant links.

Multicast VLAN Registration (MVR) is designed for applications such as Media-on-Demand that stream multicast traffic across an Ethernet network. IGMP snooping prevents the flooding of IP multicast traffic and limits bandwidth-intensive video traffic to only ports connected to subscribers.

The voice VLAN feature enables access ports to carry IP voice traffic from IP phones.

IEEE 802.1Q Tunneling (Q-in-Q) is designed for service providers carrying traffic for multiple customers across their networks.

#### Comprehensive QoS

Traffic is prioritized according to 802.1p, DSCP, IP precedence, and TCP/UDP port number, giving optimal performance to real-time applications such as voice and video.

Asymmetric bidirectional rate-limiting, per-port or per-traffic class, preserves network bandwidth and allows maximum control of network resources.

#### Enhanced Security

Port Security limits the total number of devices that can access a switch port based on MAC address, and protects against MAC flooding attacks.

IEEE 802.1X port-based or MAC-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using a standard-based RADIUS server and supports dynamic VLAN assignment and a guest VLAN.

Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on source and destination MAC addresses, IP addresses, and TCP/UDP ports. ACLs are hardware supported, so switching performance is not compromised.

Secure Shell (SSH v1.5/v2.0) and Secure Sockets Layer (SSL/HTTPS) encrypts Telnet and web access to the switch, providing secure network management.

TACACS+ 3.0 authentication, for applications such as network access or IP mobility, enables centralized control of the switch and prevents unauthorized users from altering switch configuration.

Private VLANs isolate edge ports to ensure user privacy.

#### Simple Management

An industry-standard Command Line Interface (CLI), accessed through the console port or Telnet, provides a convenient way to configure and troubleshoot the switch. In addition, the switch features a user-friendly GUI for web management.

IP Source Guard can be enabled with DHCP snooping on trunk ports with a large number of VLANs to filter and control IP traffic access to the network.

DHCP snooping provides security by filtering un-trusted DHCP messages and by building and maintaining a DHCP snooping binding table.

DHCP Option 82 is a feature that adds device information to client TCP/IP configuration requests that are relayed to a DHCP server.

## Features

### Physical Ports

24 RJ-45 10/100BASE-TX ports  
2 Combination Gigabit (RJ-45/SFP) ports  
1 RS-232 DB-9 console port

### Performance

Switching Capability: 8.8 Gbps  
Packet Buffer Size: 4 Mbit  
MAC Address Table: 8K

### L2 Features

Auto-negotiation for port speed and duplex mode

Flow Control:

- IEEE 802.3x for full-duplex mode
- Back-Pressure for half-duplex mode

Spanning Tree Protocol:

- IEEE 802.1D Spanning Tree Protocol (STP)
- IEEE 802.1w Rapid Spanning Tree Protocol (RSTP)
- IEEE 802.1s Multiple Spanning Tree Protocol (MSTP)

VLANs:

- Supports 4K IEEE 802.1Q VLANs
- Port-based VLANs
- IEEE 802.1v protocol-based VLANs\*
- Private VLAN
- GVRP
- Supports Q-in-Q
- Support voice VLANs\*

Link Aggregation:

- Static Trunk
- IEEE 802.3ad Link Aggregation Control Protocol
- Trunk groups: 13, Trunk links: 2~8

IGMP Snooping:

- IGMP v1/v2/v3 snooping
- IGMP Querier and Filtering

MVR (Multicast VLAN Registration)

Supports jumbo frames up to 10KB

- Spanning tree fast forwarding
- Loopback detection
- Auto edge port
- BPDU filter/guard
- Root guard
- G.8032 (ERPS)
- Y.1731
- 802.1ag (CFM)
- 802.3ah (OAM)

### IPv6 Features

IPv4/IPv6 dual-protocol stack  
IPv6 Address Types Stack: Unicast  
IPv6 Neighbor Discovery  
SNMP over IPv6  
HTTP over IPv6  
Remote IPv6 ping  
IPv6 Syslog support  
IPv6 SNMP support  
IPv6 Telnet support  
IPv6 TFTP support  
Remote IPv6 ping  
IPv6 ACL

### QoS Features

Priority Queues: 4 hardware queues per port  
Traffic classification based on IEEE 802.1p CoS, IP Precedence, DSCP, TCP/UDP port number  
Supports WRR and Strict scheduling  
Rate Limiting (Ingress and Egress, per port base)

- FE: Resolution 64 Kbps ~ 100 Mbps
- GE: Resolution 64 Kbps ~ 1000 Mbps

### Security

Port security  
Support multiple IEEE 802.1X port-based and MAC access control  
Dynamic VLAN Assignment, Auto QoS, Auto ACL  
MAC-based authentication, Web authentication  
Voice VLAN, Guest VLAN  
RADIUS authentication  
TACACS+ authorization and accounting  
TACACS+ 3.0  
L2/L3/L4 Access Control List  
SSH (v1.5/v2.0)  
SSL  
STP BPDU port protection

### Management

Switch Management:

- CLI via console port or Telnet
- Web management
- SNMP v1, v2c, v3

Firmware and Configuration:

- Firmware upgrade via TFTP server
- Multiple configuration files
- Configuration file upload/download via TFTP server

Supports RMON (groups 1, 2, 3 and 9)

Supports BOOTP, DHCP client for IP address assignment

Supports DHCP Option 82, DHCP Snooping

Supports SNMP

Event/Error Log/Syslog, SMTP

Supports LLDP (802.1ab), UPnP

Support IP Source Guard

(Optional) ECView Pro, powerful network management software that maximizes the managed capabilities of Edge-Core devices with:

- Topology Management
- Performance Management
- Configuration Management
- Event Management
- SNMP Management

IP source guard

Port mirroring

Dynamic ARP inspection (DAI)

IPv6 management

### Mechanical

Dimensions (W x D x H): 440 mm x 210 mm x 44 mm

Weight: 1.7 kg

LED Indicators: Port, Uplink, System, Diagnostic

### Safety

UL (CSA 22.2 NO 60950-1 & UL60950-1)

CB (IEC60950-1)

### Electromagnetic Compatibility

CE Mark

FCC Class A

CISPR Class A

### Environmental Specifications

Temperature:

- IEC 68-2-14
- 0°C to 50°C (standard operating)
- -40°C to 70°C (non-operating)

Humidity: 10% to 90% (non-condensing)

Vibration: IEC 68-2-36, IEC 68-2-6

Shock: IEC 68-2-29

Drop: IEC 68-2-32

### Power Supply

AC Power

- 100 to 240 V, 50-60 Hz, 0.8 A

Power Supply

- Internal, auto-ranging transformer: 100 to 240 VAC, 50 to 60 Hz

### Warranty

Please check www.edge-core.com for the warranty terms in your country

## Ordering Information

### Optional Accessories

ET4201-SX  
ET4201-LX  
ET4201-LHX  
ET4201-ZX  
ECView Pro

### Product Description

1 Gbps, Small Form Factor Pluggable (Distance: 500 m; Wavelength: 850 nm)  
1 Gbps, Small Form Factor Pluggable (Distance: 10 km; Wavelength: 1310 nm)  
1 Gbps, Small Form Factor Pluggable (Distance: 40 km; Wavelength: 1310 nm)  
1 Gbps, Small Form Factor Pluggable (Distance: 80 km; Wavelength: 1550 nm)  
SNMP Network Management Software \* Future Release