

ECS4610-26T/ECS4610-50T

Managed 24/48-Port Gigabit Ethernet Stackable L3 Switch with 4 Combo SFP Slots



Product Overview

The Edge-Core ECS4610 Series includes two stackable Gigabit Ethernet routing switches with a choice of 24 or 48 Gigabit 10/100/1000BASE-T ports, four combination Gigabit Ethernet SFP slots, two optional 10 Gigabit Ethernet slots, and two stacking ports on the rear panel. The ECS4610 Series is ideal for service provider edge aggregation, enterprise wiring closets, data center aggregation, and network core deployment. It provides high performance, resilient stacking, wire-speed L2 switching and L3 routing, comprehensive QoS, and advanced security to deliver the scalability and resiliency to increase your company's productivity while reducing operation costs.

Key Features and Benefits

Resilient Stacking up to 8 Units

The Edge-Core ECS4610 Series currently includes two different models, the ECS4610-26T and ECS4610-50T, with dual optional 10 Gigabit Ethernet uplinks. The two models provide full non-blocking performance to meet network demands for voice and video streaming. Optional 10GBASE-XFP transceivers can support fiber uplinks up to 40 km.

The Edge-Core ECS4610 Series provides two stacking ports for hardware stacking with up to 320 Gbps throughput. Any combination of ECS4610 Series units can be stacked up to 8 units high, or to a maximum of 400 ports. The stack acts as a single switching unit that is managed by a master switch, elected from one of the member switches. The master switch automatically creates and updates all the switching and optional routing tables. A working stack can add new members or delete old ones without service interruption.

High Availability

With IEEE 802.1w Rapid Spanning Tree Protocol, the Edge-Core ECS4610 Series provides a loop-free network and redundant links to the core network with rapid convergence of less than 2 seconds. IEEE 802.1s Multiple Spanning Tree Protocol allows a Spanning Tree instance per VLAN, for Layer 2 load sharing on redundant links.

The Edge-Core 4610 Series supports IEEE 802.3ad Link Aggregation Control Protocol (LACP). The switches increase bandwidth by automatically aggregating several physical links together as a logical trunk and offer load balancing and fault tolerance for uplink connections.

Adding an optional redundant power supply ensures that the Edge-Core ECS4610 Series remains stable to support today's high-availability, mission-critical environments.

Comprehensive QoS

The Edge-Core ECS4610 Series offers advanced QoS for marking, classification, and scheduling to deliver best-in-class performance for data, voice, and video traffic at wire speed. Eight egress queues per port enable differentiated management of up to eight traffic types across the stack. Traffic is prioritized according to 802.1p, DSCP, IP precedence, and TCP/UDP port number to provide optimal performance for real-time applications. Weighted Round Robin (WRR) and strict priority ensure differential prioritization of packet flows and avoid congestion of ingress and egress queues.

With bidirectional rate-limiting, per port or traffic class, the Edge-Core ECS4610 Series preserves network bandwidth and allows full control of network resources.

Enhanced Security

The Edge-Core ECS4610 Series provides enhanced security features for connectivity and access control, including ACLs, authentication, and port-level security with IEEE 802.1X. Access Control Lists (ACLs) can be used to restrict access to sensitive network resources by denying packets based on L2/L3/L4 headers. SSH and RADIUS authentication protect data communications and ensure data privacy. IEEE 802.1X port-based access control ensures dynamic, port-based security, and user authentication for network access.

IP source guard prevents a malicious user from spoofing or taking over another user's IP address by creating a binding table between client's IP and MAC address, port, and VLAN.

Simplified Management

For IP multicast traffic, the Edge-Core 4610 Series enables IGMP snooping to provide fast client joins and leaves of multicast streams. The switches prevent flooding of IP multicast traffic, and limit bandwidth-intensive video traffic to only the subscribers.

The Edge-Core ECS4610 Series supports IPv6 management functions in SNMP, HTTP, Telnet, TFTP, ICMP, SSH, and IPv6 QoS remapping when connecting to the switch or stack.

The Edge-Core ECS4610 Series can be managed through an industry-standard Command Line Interface (CLI) that provides a common look and feel to reduce training and operating costs. The switches also provide an easy-to-use web interface through a standard web browser.

Four-group RMON is supported to collect traffic statistics and run network diagnostics. The switches can also backup and restore firmware and configuration files via TFTP.

Advanced IPv6 and IPv4 Routing

The Edge-Core ECS4610 Series supports hardware-based IPv6 and IPv4 routing for maximum performance. The switches provide a seamless migration path from IPv4 to IPv6 for future network upgrades and investment protection.

Advanced routing protocols such as RIP and OSPF provide dynamic routing by exchanging routing information with other Layer 3 switches or routers. Multicast routing is supported under independent multicast protocols, including PIM-DM and PIM-SM.

Features

Physical Ports

20 or 44 RJ-45 10/100/1000BASE-T ports, with auto-negotiation
 4 Combination (RJ-45/SFP) Gigabit Ethernet ports
 2 10GBASE extender module slots for XFP transceivers
 2 slots for stacking transceivers
 1 RJ-45 console port
 1 Redundant power supply connector

Performance

Switching Capacity: 128 Gbps/176 Gbps
 Forwarding Rate: 95.2 Mpps/130.9 Mpps
 MAC Address Table Size: 16K
 Packet Buffer Size: 2 MB

L2 Features

Spanning Tree

- Loopback detection
- Auto edge port
- BPDU filter/guard

 VLAN

- IP subnet based VLAN
- Private VLAN Isolated
- Private VLAN
- GVRP/GARP
- 802.1v protocol
- Voice VLAN
- VLAN translation
- IPv6 VLANs
- VLAN Trunking

 Jumbo Frame : 9K
 IGMP Snooping v1/v2/v3
 Select Q-in-Q

L3 Features

Host table: 8K
 Route table: 8K
 Static route table: 512
 Multicast table: 1K
 Unicast routing

- Static unicast routes
- RIP v1/v2
- OSPF
- BGP

 Multicast routing

- PIM-DM
- PIM-SM
- IGMP v1/v2/v3
- IGMP v3 proxy

 IP Redundancy
 Proxy ARP
 UDP Helper

QoS Features

Priority Queues: 8 hardware queues per port
 Traffic classification based on IEEE 802.1p CoS, IP Precedence, DSCP,
 TCP/UDP port number, Access Control List, marking
 DiffServ
 Supports WRR and strict priority
 Port rate limiting

Security

Port security
 IP Source Guard
 Supports IEEE 802.1X port-based and MAC-based access control
 IP filter configuration for management interface (SNMP, Telnet, Web)
 RADIUS authentication
 Access Control List
 SSH v2
 HTTPS/SSL
 MAC filter
 Dynamic ARP Inspection
 Link detection

IPv6 Features

IPv4/IPv6 Dual Protocol Stack
 IPv6 Address Types : Unicast, Multicast
 ICMPv6
 ICMPv6 Redirect
 IPv6 Path MTU Discovery
 IPv6 Neighbor Discovery
 SNMP over IPv6
 HTTP over IPv6
 SSH over IPv6
 Support IPv6 Telnet
 Support IPv6 DNS Resolver
 Support IPv6 syslog
 Support IPv6 SNTP
 Support IPv6 TFTP
 Remote IPv6 ping
 Ping over IPv6
 Trace route over IPv6
 IPv6 DHCP relay
 sFlow over IPv6
 IPv6 ACL
 IPv6 DiffServ
 PIM-DMv6
 PIM-SMv6
 MVRv6

Management

Switch Management:

- CLI via console port or Telnet
- Web management
- SNMP v1, v2c, v3
- IGMP snooping (v1/v2)

 Firmware and Configuration:

- Dual firmware images
- Firmware upgrade via TFTP/FTP/Xmodem
- Multiple configuration files
- Configuration file upload/download via TFTP/FTP server

 Supports RMON (groups 1, 2, 3 and 9)
 Supports BOOTP, DHCP for IP address assignment
 DHCP Snooping
 DHCP option 66, 67
 Supports SNTP
 Supports event/error log, system log
 Cable diagnostics
 ATC traffic control
 Delay reload
 sFlow
 CPU Process Utilization
 Cable Diagnostic
 IP Clustering
 Port Mirroring

SNMP Standards

RFC 1907 SNMPv2-MIB (MIB-II)
 RFC 2011 IP-MIB (MIB-II)
 RFC 2012 TCP-MIB (MIB-II)
 RFC 2013 UDP-MIB (MIB-II)
 IEEE 802.1X IEEE8021-PAE-MIB
 RFC 1493 Bridge MIB
 RFC 2863 IF-MIB
 RFC 2819 RMON MIB
 RFC 2618 RADIUS MIB
 RFC 2665 Etherlike MIB
 RFC 2737 Entity MIB
 RFC 2674 P-bridge, Q-bridge
 V-Bridge MIB
 RFC 3036 MAU MIB
 RFC 1612 DNS Reslover MIB
 RFC 3411 SNMP Framework
 RFC 3412 SNMP MPD MIB
 RFC 3413 SNMP Target MIB, SNMP Notify MIB
 RFC 3415 SNMP View-Based ACM MIB
 SNMP Trap Supported:
 RFC 1215, 1907, 2863, 1493, 1757, 2819
 Private MIB

Features

Electrical

- Power Consumption (Max.):
 ECS4610-26T
- 49.6 Watts (without expansion XFP modules)
 - 63.96 Watts (with two expansion XFP modules)
- ECS4610-50T
- 98.16 Watts (without expansion XFP modules)
 - 104.16 Watts (with two expansion XFP modules)
- Power characteristics:
- Voltage: 100-240V AC auto-ranging
 - Frequency: 47-63Hz
- Current:
- ECS4610-26T
- 0.58 A @ 110 VAC (without expansion XFP modules)
 - 0.74 A @ 110 VAC (with two expansion XFP modules)
 - 0.312 A @ 240 VAC (without expansion XFP modules)
 - 0.375 A @ 240 VAC (with two expansion XFP modules)
- ECS4610-50T
- 0.995 A @ 110 VAC (without expansion XFP modules)
 - 1.21 A @ 110 VAC (with two expansion XFP modules)
 - 0.54 A @ 240 VAC (without expansion XFP modules)
 - 0.605 A @ 240 VAC (with two expansion XFP modules)

Standards & Compliance

- IEEE 802.3-2005
- Ethernet, Fast Ethernet, Gigabit Ethernet
- Full-duplex flow control
- IEEE 802.3ae 10 Gigabit Ethernet
- IEEE 802.3D Spanning Tree Protocol
- IEEE 802.1w Rapid Spanning Tree Protocol
- IEEE 802.1s Multiple Spanning Tree Protocol
- IEEE 802.1Q Virtual LAN
- ISO/IEC 8802-3 CSMA/CD

Reliability

- ECS4610-26T
- MTBF 25°C 146,894 hours
 - MTBF 50°C 65,293 hours
- ECS4610-50T
- MTBF 25°C 125,128 hours
 - MTBF 55°C 56,627 hours

Electromagnetic Compatibility

- CE Mark (EN55022 (CISPR 22) Class A
- EN 61000-3/2/3
- FCC Class A
- VCCI Class A

Environmental Specifications

- Temperature:
- IEC 68-2-14
 - 0°C to 50°C (standard operating)
 - -40°C to 70°C (non-operating)
- Humidity: 5% to 95% (non-condensing)
- Vibration: IEC 68-2-36, IEC 68-2-6
- Shock: IEC 68-2-29
- Drop: IEC 68-2-32

Mechanical

- Dimensions (H x W x D): 4.4 x 44 x 41.5 cm (1.7 x 17.3 x 16.3 inch)
- LED Indicators: Port, Uplink, System, Diagnostic
- AC Power Input: 100 ~ 240 VAC, 50 ~ 60 Hz
- Weight:
- ECS4610-26T: 5.7 kg (12.6 lbs)
 - ECS4610-50T: 6.1 kg (13.4 lbs)

Safety

- UL60950-1 & CSA 60950-1
- IEC 60950-1 & EN 60950-1

Warranty

Please check www.edge-core.com for the warranty terms in your country.

For More Information

To find out more about Edge-Core Networks products and solutions, visit www.edge-core.com

About Edge-Core Networks

Edge-Core Networks is in the business of providing innovative network solutions. In the service provider network, in the data center or in the cloud, Edge-Core Networks delivers the software and systems that transform the way the world connects. Edge-Core Networks serves customers and partners worldwide. Additional information can be found at www.edge-core.com.

To purchase Edge-Core Networks solutions, please contact your Edge-Core Networks representative at 886 3 563 8888 or authorized reseller.

© Copyright 2012 Edge-Core Networks Corp. The information contained herein is subject to change without notice. This document is for informational purposes only and does not set forth any warranty, expressed or implied, concerning any equipment, equipment feature, or service offered by Edge-Core Networks. Edge-Core Networks shall not be liable for technical or editorial errors or omissions contained herein.

Ordering Information

RPS600WA

- ECS4600-STACABLE-S
- ECS4600-STACABLE-L
- EM4626H-XG-XFP
- ET4201-SX
- ET4201-LX
- ET4201-LHX
- ET4201-ZX
- ET5302-SR
- ES5302-LR
- ET5302-ER
- EM4626H-XG10GSFP+
- ET5402-SR
- ET5402-LR

Network Management System

- 4 DC output redundant power supply connectors (Supports max. power output 150W/12V per port)
- Stacking cable for ECS4610-26T/ECS4610-50T, 30cm
- Stacking cable for ECS4610-26T/ECS4610-50T, 130cm
- 10G XFP module
- 1000BASE-SX Multi mode SFP transceiver, up to 500m (850nm)
- 1000BASE-LX Single mode SFP transceiver, up to 10Km (1310nm)
- 1000BASE-LHX Single mode SFP transceiver, up to 40Km (1310nm)
- 1000BASE-ZX Single mode SFP transceiver, up to 80Km (1550nm)
- 10G XFP transceiver, 300m, 850nm, LC connector (Multi-mode)
- 10G XFP transceiver, 10km, 1310nm, LC connector (Single-mode)
- 10G XFP transceiver, 10km, 1550nm, LC connector (Single-mode)
- 10G SFP+ module
- 10G SFP+ transceiver, 300m, 850nm, LC connector (Multi-mode)
- 10G SFP+ transceiver, 10km, 1310nm, LC connector (Single-mode)

ECView Pro Network Management Software